







DESCRIPTION	MODEL		NET NO VAT € ea.	PRICE Incl. VAT 22% € ea.
TURNTABLES				
Turntable with extreme performance can mount up to four 9" and / or 12" arms - external electronics with filtered and stabilized power supply and continuous rotation speed control. Wow and flutter not measurable thanks to external controller with optical detector. Standard equipment 1 arm 9". Version with 1 arm 9" and 1 arm 12" (see image) price on request Weight 28 kg.			GLADIATORE	8.106,56 9.890,00
Belt drive turntable - Rotation speed precision: $\pm 0.8\%$ - Wow and Flutter: $\leq 0.15\%$ - Signal to noise ratio: -68dB - outputs: MM Phono and Line - High quality internal MM Phono Pre-amplifier - Aluminum outer platter - Aluminum straight arm - 33/45 & On/Off selector - Effective arm length: 8.6" (218.5mm) - Counterweight antiskating - Opto/electronic functions for start and stop - Mobile Magnet cartridge (AT3600L) - Stylus radius of the stylus 0.015mm - Plexi cover hood - External power supply - Dimensions (W x H x D): 415x140x360 mm - black high gloss or wood finish - Weight: 7.5kg			GD900	349,18 426,00
VACUUM TUBE INTEGRATED AMPLIFIERS				
Integrated stereo valve amplifier 2 x 55W RMS / 8 Ω - Valves: KT-88x4, 12AX7x2, 6SN7x2 - Input.: 3 line, 1 Phono MM, 1 Balanced, 1 Direct Power Amp - Freq. resp.: 20Hz \div 50kHz (5W) - THD: 0.1% (10W) - S / N (line): 86dB - Input. Sens. (line): 300mV - Input. Imped.(line): 80k Ω - Input. Imped. (XLR): 95k Ω - Phono MM: Imped./capacity 47k Ω / 68pF, sens.: 3.5mV, S / N: 78dB - Speakers imped.: 4 / 8 Ω - Remote Control - Adj. external bias with dedicated tool - Max consumption 320W - Voltage supply.: 115 / 230V-50 / 60Hz - Dim.: 430x350x220mm (wxdxh) - valves cover grille with plexi - Weight: 30kg			AP990C	2.909,84 3.550,00
Same as above - but Valves KT-120x4			AP990C/2	3.000,00 3.660,00
Same as above - but Valves KT-150x4			AP990C/5	3.178,69 3.878,00
HYBRID INTEGRATED AMPLIFIER				
Integrated hybrid stereo amplifier 2 x 70W RMS / 8 Ω - Valves: 2x6N1 - Freq. resp.: 20Hz \div 50kHz - THD: <0.05% - Gain Line: 34dB - Gain Phono: 74dB - S / N (line): 86dB - Input. Imped. (line): 80k Ω - Input. Phono MM: 47k Ω / 68pF - Speakers Imped.: 4 to 8 Ω - Headphone Imped.: 32 \div 200 Ω - USB Input. 24bit 96kHz x PC / MAC and smartphone / tablet OTG - Wireless Receiver 4.0 - Remote control - Dim.: 430x350x120mm (WxDxH) - Weight: 18kg			A-165 USB	1.124,59 1.372,00

DESCRIPTION	MODEL	NET NO VAT € ea.	PRICE Incl. VAT 22% € ea.	
PREAMPLIFIER - POWER AMPLIFIER - MINI HI-END				
<p>Hybrid Preamplifier / Headphone Amplifier with 384 kHz / 32 bit USB DAC DSD - Inputs: USB in, SPDIF in, AUX in, Line in, Phono MM / MC - Outputs: headphones, SPDIF, subwoofer, line - Supports DSD 2.8 / 5.6MHz, PCM 384kHz / 32 bit, native DSD or DoP - Asynchronous transfer mode - Works with Apple (with camera kit) and Android (with OTG cable) - Loudness EQ - Balance - Tri-Band tone control - Headphone output power (1kHz 1 ch): 210mW / 16Ω, 190mW / 32Ω - Headphone accepted impedance: 16 ÷ 600Ω - DAC: SABER9018Q2C - Valve 12AU7 - Analog volume control - Supports ASIO - Power supply 24V - LED indicators for DSD / PCM and Active input - De-pop function - Metal case - System requirements: Windows 10 / 8.x / 7, Vista 32/64-bit, XP 32bit, MAC OSX, iOS and Android with USB audio driver - PC with USB 2.0 - Dimensions: 115X 117X49mm - Weight: 586 g</p>		C-101	520,49	635,00
<p>Class D stereo amplifier - Input: line 3.5 mm - Outputs: Speakers, Pre out, Headphone output x 2 - 30 x 2 LED signal level indic. (4 modes) - Headphone / speaker selector - Loudness EQ - Power: 2x30W (8Ω), 2x50W (4Ω) - Headset Power: 270mW / 16Ω, 450mW / 32Ω at 1kHz - Impedance accepted headphone: 16 ÷ 600Ω - Frequency response: 20Hz ÷ 20kHz (± 0.5 dB) - Integrated de-pop function - Power supply: 24V / 5A - Metal cabinet - Dimensions: 115X136X39mm - Weight 567 g</p>		P-101	326,23	398,00
PREAMPLIFIER - MONO POWER AMPLIFIER - HI-END				
<p>Dual Monoaural Balanced preamplifier - Line inputs: RCA x2 XLR x1 - Outputs: RCA x2 XLR x1 (selectable) - Matrix Relay volume circuit - Frequency response: 5Hz ÷ 200kHz -0.2dB - Channel separation:> 115dB - THD: 0.0009% @ 1kHz 1VRMS input - Max input voltage 3VRMS - Max output voltage 20.2VRMS - Remote control - Power supply: AC 117V / 230V - Consumption: 28W - Dimensions (WxDxH): 430 x 350 x 90 mm - Weight: 10 kg</p>		C-102	3.193,44	3.896,00
<p>Mono power amplifier 250 W RMS 8 Ω - 420 W RMS 4 Ω - input RCA and balanced - input adjustment trigger - Vumeter - black - Dimensions (WxDxH): 265 x 205 x 330 mm - Weight 26kg</p>		M-250	3.583,61	4.372,00
HYBRID PHONO MM-MC PREAMPLIFIER				
<p>Phono MM / MC hybrid preamplifier - Valve 1 x ECC85 (6N1) 1 x 12AX7 - Gain 63dB MC adjust. 66 to 60dB - Load capacity 10-20-47-100pF MM - MM impedance 47kΩ - resistive load MC 20/50/75/100/200 / 500Ω - subsonic filter 20-40 Hz - Freq. resp. 10Hz ÷ 25kHz ± 2dB - dim .: 380x280x125mm - black color - Weight 8kg</p>		LP-X1	1.547,54	1.888,00

DESCRIPTION	MODEL		
BLUETOOTH RECEIVER/TRANSMITTER HI DEFINITION			
<p>BT Chipset CR8675 receiver / transmitter with BT version 5.0 A2DP / ACRCP - Range of action: 30 meters (open area) - 450mA battery with 18 hours autonomy - Distortion rate: <1% - Frequency response: 40Hz-18kHz - Audio codec SBC / AAC 7 aptX / aptX Low Latency / aptX HD - Supports sample rates up to 96kHz - the HDP-1 can be combined with 2 HDP-1 receivers in TX mode - Supports TWS (True Wireless Stereo) in RX mode - OPTICAL input and output in both modes - USB audio input in TX mode - Dimensions: 68 x 68 x 20 mm (LxWxH) - Weight: 53.5 g</p>		HDP-1	116,00
	 		
NETWORK PLAYER			
<p>Stream same or different music to all speakers - Stream music from home NAS network - ESS hifi DAC for purest sound - Decoding Hi-Res Audio up to 24bit/192kHz - One click to your favorite library - Sleep timer - Use external DAC via SPDIF/Optical output - Play music from USB storage - Left/Right stereo speaker pairing - Set your favorite music playlist as alarm - Connect wired analog sources or stream wirelessly - WPS Smart-link technology for easy and quick connection - Stream music from home UPnP network - Stream your hifi music to your speakers - Alternative LAN connection for perfect Hi-Res streaming - Portable and mobile stream anywhere -</p>		NP-1	318,00
			
SPEAKERS - BLACK ROSA Series			
<p>Monitor speaker - Frequency Response: 34Hz-22kHz@-3dB - Sensitivity: 86dB - Crossover Frequency: 2.5kHz - Design Principle: 2-Way Bass Reflex, - Aluminum Cabinet - Tweeter: Silk Screen Dome - Woofer: 5.5" Driver (Carbon Fiber +PMI+Fiberglass Sandwich Cone) - Impedance: 8ohms - Power Rating: 100W - Dimensions: 162 x 238 x 240mm (WxHxD) - Weight: 5.5kg each</p>		HY-1	698,00

This price list replaces and cancels the previous ones, price changes are possible without prior notice.

EUROPEAN DISTRIBUTION
AUDIO4STEREOLAND srls

Office/warehouse/laboratory : Loc. Incugnate n.16 20060 Truccazzano Milan-Italy - Tel./fax 0295838428
 Show room: Via Aosta 29 - 39100 Bolzano Tel. 0471278691
 www.aeron-audio.it - www.a4s.info - email: info@aeron-audio.info - info@a4s.info